# LENCIR LED | SURFACE MOUNT

# SM567710 / SM567712 / SM567714 / SM567780 / SM567784

- Die Cast Aluminum
- Size options between 5", 7" and 10"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces

• Suitable for Closets according to NEC Section 410.8 & 410.16

• Available in White (WT), Bronze (BZ), and Satin Nickel (SN)

• Dimmable with Triac and ELV Dimmers

- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- ETL/cETL IP65

Job Name:	Job Type:
Quantity:	Comments:





SM567784WTWT Lencir LED 7" RD w/ 1.5 hours Emergency Back Up











### PRODUCT DESCRIPTION

Lencir was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Lencir brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.


### **FINISHES OPTIONS:**


White (WT)

Bronze (BZ)

Satin Nickel (SN)







## **MEASUREMENTS**

MODEL	DIMENSION	HANGING WEIGHT
SM567710	5"D x 0.5"H	0.88 lb
SM567712	7"D x 0.5"H	1.21 lb
SM567780	7"D x 1.25"H	
SM567784	7"D x 1.75"H	
SM567714	10"D x 0.5"H	1.75 lb

#### LAMPING

			LUMENS	COL		
MODEL	BULB TYPE	CRI	INIT DEL	TEMP.	DIMMABLE	INPUT
*SM567710	10W LED (Integrated)	90+	700 600	3000K	ELV	120V
*SM567712	15W LED (Integrated)	90+	1050 900	3000K	ELV	120V
*SM567780	Add on shell					
*SM567784	15W LED (Integrated)	90+	1100 900	3000K	ELV	120V
*SM567714	20W LED (Integrated)	90+	1400 1200	3000K	ELV	120V

<sup>\*120-277</sup>V input and 0-10V dimming available upon request

Always consult a qualified electrician before installing any lighting product

### MATERIAL:

Die Cast Aluminum PMMA Acrylic Diffuser

# **AVAILABLE SIZES:**

5" | 7" | 10"

### **RATINGS:**

ETL/cETL IP65 Wet Location **Energy Star** Title 24 JA8 compliant ADA Dimmable Closets Rated: 410.8 & 410.16













### **ADDITIONAL:** RATED LIFE: 50,000 Hours

OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online

