


PRODUCT DESCRIPTION

Step and pathway lighting suitable for interior or exterior application. Designed to install into a single gang box and is line voltage so additional transformers are not needed. Available in Aluminum, White, Black, or Bronze and both horizontal wide beam or vertical narrow beam spread.



MEASUREMENTS

 DIMENSION
 : 5" W x 3" H x 1.5" Ext

 MAX OAH
 : 3" W x 5" H

 HANGING WEIGHT
 : 0.77 lb

LAMPING

INPUT VOLTAGE : 120V LUMENS : 280 Rated (112 Del.)

BULB : 4W LED PCB Integrated , 4W Total

BULB INCLUDED : (Integrated)

DIMMABLE : No
CRI : 80+ CRI
COLOR_TEMP : 3000K
LIGHTING_DIRECTION : Down

FINISHES OPTION



Brushed Aluminum (AL)

White (WT)

MATERIAL

Aluminum

RATINGS

cETLus Wet Location



ADDITIONAL

INSTALL UP/DOWN: Up RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Job Name	Job Type:
Quantity:	Comments