
Quantity:



#### **PRODUCT DESCRIPTION**

Step and pathway lighting suitable for interior or exterior application. Designed to install into a single gang box and is line voltage so additional transformers are not needed. Available in Aluminum, White, Black, or Bronze and both horizontal wide beam or vertical narrow beam spread.



## MEASUREMENTS DIMENSION

MAX OAH

LAMPING

2.5"

"HCO

: 3" W x 5" H x 2.25" Ext : 5" W x 3" H : 0.77 lb HANGING WEIGHT

## INPUT VOLTAGE

LUMENS BULB **BULB INCLUDED** 

DIMMABLE CRI

LIGHTING\_DIRECTION : Down

:120V : 280 Rated (112 Del.)

: 1 x 4W LED PCB Integrated , 4W Total : (Integrated) :No : 80+ CRI COLOR\_TEMP : 3000K

# FINISHES OPTION

# Black (BK) Bronze (BZ)

Brushed Aluminum (AL)

White (WT)

# MATERIAL

Aluminum

### RATINGS CETLUS Wet Location



# ADDITIONAL

INSTALL UP/DOWN: Up RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order\_ [Project Name] / [Specifier/Designer]"

All samples are subject to Studio M approval and must show proof of project and/or explanation.