


PRODUCT DESCRIPTION

Step and pathway lighting suitable for interior or exterior application. Designed to install into a single gang box and is line voltage so additional transformers are not needed. Available in Aluminum, White, Black, or Bronze and both horizontal wide beam or vertical narrow beam spread.



MEASUREMENTS

LAMPING

LUMENS

BULB

CRI

2.5″

"HCO

: 3" W x 5" H x 2.25" Ext DIMENSION : 5" W x 3" H MAX OAH : 0.77 lb HANGING WEIGHT INPUT VOLTAGE :120V : 280 Rated (112 Del.) : 1 x 4W LED PCB Integrated , 4W Total **BULB INCLUDED** : (Integrated) DIMMABLE :No : 80+ CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION : Down

FINISHES OPTION

Black (BK) Bronze (BZ) Brushed Aluminum (AL) White (WT)

MATERIAL

Aluminum

RATINGS CETLUS Wet Location



ADDITIONAL

INSTALL UP/DOWN: Up RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name: Job Type: Quantity: Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]"

All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Type:

Quantity: