SM660010BZGTGLD

- ETL/cETL
- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)

Job Name:	Job Type:
Quantity:	Comments:





PRODUCT DESCRIPTION

Maxim Lighting is proud to add the Weave fandelier to one of our most-sought after signature lighting collections. The Weave fandelier features a stunning ring of metal bands woven together and finished with hand painted Bronzed Gilt on the outside and contrasting Gold Leaf on the inside. LED lighting illuminates the space with a warm and inviting glow while the seamlessly integrated fan circulates the air for optimal comfort.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs





MEASUREMENTS

DIMENSIONS : 33"D x 18.5"H
CANOPY : 7"D x 2.75"H
HANGING WEIGHT : 28.09 lb

BLADE : 3 Blades with 22" span

BLADE PITCH : Varying BLADE TO CEILING : 13.75"H

LAMPING

INPUT VOLTAGE : 120V
LUMENS : 4158 Rated (2000 Del.)
BULBS : 46W PCB LED (Bulb included)

DIMMABLE : Yes
CRI : 80+
COLOR TEMP : 3000K
MOTOR TYPE : DC Motor

AIRFLOW

SPEEDS : 6
AIRFLOW CFM : 5057
ELECTRICITY USE : 31.90W
AIRFLOW EFFICIENCY: 158.5

FINISHES OPTIONS:

Bronze Gilt / Gold (BZGTGLD)



MATERIAL:

Steel Aluminium

Polypropelene Fan Blades

INCLUDES

- Wall Mountable Remote Control
- 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118BZGT) • 24" (FRD0124BZGT)
- 24" (FRD0124BZG
- 30" (FRD0130BZGT)
- 36" (FRD0136BZGT)

RATINGS:

ETL cETL Dry Location Title 20





ADDITIONAL:

RATED LIFE: 35,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F)

LIGHTING DIRECTION: Out

