SOLITAIRE | FANDELIER SM660013SM

• ETL/cETL


- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)
- Frosted CA LED bulbs included




PRODUCT DESCRIPTION

The creme de la creme - the Solitaire. This romantic fandelier delivers luxury appeal and timeless sophistication. The Solitaire fandelier features curved arms that lift a crown of six candle-style lamps. It is adorned with six large marquise cut crystals and six circular cut crystals that illuminate the surroundings in a regal display of light. This beautiful Fandelier is hand-painted in a Silver Mist finish creating a sophisticated wrought-iron appearance.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:
- Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs





MEASUREMENTS

 DIMENSIONS
 : 30.75"D x 18.75"H

 CANOPY
 : 6.75"D x 2.75"H

 HANGING WEIGHT
 : 20.75 lb

 BLADE
 : 3 Blades with 22" span

 BLADE PITCH
 : Varying

 BLADE TO CEILING
 : 9.75"H

INPUT VOLTAGE LUMENS BULB DIMMABLE CRI COLOR TEMP MOTOR TYPE : 120V : 1988 Rated (1680 Del.) : (6) 4W LED (Bulb Included), 24W Total : Yes : 80+ : 3000K : DC Motor

AIRFLOW

SPEEDS : 6 AIRFLOW CFM : 5057 ELECTRICITY USE : 31.90W AIRFLOW EFFICIENCY: 158.5

STUDIO•M

For Modifications or Customizations, please email contract@studiomlighting.com

For Sample Request, please email order@studiomlighting.com with subject line: "Sample Order_[Project Name]/[Specifier/Designer]" All Samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments:

FINISHES OPTIONS:

Silver Mist (SM)

MATERIAL:

Steel K9 Crystal Polypropelene Fan Blades

INCLUDES

Wall Mountable Remote Control
 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118SM)
- 24" (FRD0124SM)
- 30" (FRD0130SM)
- 36" (FRD0136SM)

RATINGS:

ETL cETL Dry Location Title 20



ADDITIONAL: RATED LIFE: 20,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) LIGHTING DIRECTION: Down