



## **PRODUCT DESCRIPTION**

Excellently crafted mini spotlights are ideal for highlighting spaces and providing ambient, articulating light. A knurled section of aluminum tubing meets a larger smooth surfaced aluminum housing. Recessed within this housing is a high powered, low voltage LED light source. Either wire multiple in series or individually to various accessories not provided.

MEASUREMENTS DIMENSION

MAX OAH HANGING WEIGHT

## LAMPING

INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR\_TEMP LIGHTING\_DIRECTION : 2" W x 5.75" H x 3.5" Ext : 2" W x 2" H : 14.55 lb

: 24V : 300 Rated (200 Del.) : 5W LED DC Integrated , 5W Total : (Integrated) : Triac or ELV : 90 CRI : 2700K : Directional

## FINISHES OPTION



MATERIAL Aluminium, PMMA

RATINGS CETLus Wet Location ADA



## ADDITIONAL

INSTALL UP/DOWN: Up/Down RATED LIFE 45000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order\_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments