





PRODUCT DESCRIPTION

Cylinders of White cased glass are mounted onto a cast aluminum frame of Satin Nickel or Polished Chrome. LED modules evenly illuminate and provide soft yet ample illumination. Multi volt input is standard which allows for installation into commercial applications.

MEASUREMENTS

DIMENSION : 24" W x 4.75" H x 3.5" Ext **BACK PLATE** : 7" W x 4.75" H x 2.25" HCO

HANGING WEIGHT : 3.9 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 1,520 Rated (1,250 Del.)

BULB : 16W LED PCB Integrated, 16W Total

BULB INCLUDED : (Integrated) DIMMABLE : at 120V with ELV

CRI : 90 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION : Up/Down

FINISHES OPTION



GLASS

White WT

MATERIAL

Aluminum, Glass

RATINGS

cETLus Damp Location







ADDITIONAL

INSTALL UP/DOWN: Any SLOPE: RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Job Name:	Job Type:
Quantity:	Comments