Optic | SM562116WTPC

PRODUCT DESCRIPTION

Cylinders of White cased glass are mounted onto a cast aluminum frame of Satin Nickel or Polished Chrome. LED modules evenly illuminate and provide soft yet ample illumination. Multi volt input is standard which allows for installation into commercial applications.

MEASUREMENTS

DIMENSION	: 30" W x 4.75" H x 3.5" Ext
BACK PLATE	: 7" W x 4.75" H x 2.25" HCO
HANGING WEIGHT	: 5.03 lb

LAMPING

INPUT VOLTAGE	: 120-277V
LUMENS	: 1,900 Rated (1,550 Del.)
BULB	: 20W LED PCB Integrated , 20W Total
BULB INCLUDED	: (Integrated)
DIMMABLE	: Only at 120V with ELV
CRI	: 90 CRI
COLOR_TEMP	: 3000K
LIGHTING_DIRECTION	: Up/Down

FINISHES OPTION

Polished Chrome (PC)

Satin Nickel (SN)

GLASS
White WT

MATERIAL
Aluminum, Glass

RATINGS
cETLus
Damp Location
Energy Star
ADA

ADDITIONAL
INSTALL UP/DOWN: Any
RATED LIFE 50000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

STUDIO•M

Modifications or Customizations: Please email contract@studiomlighing.com
Sample Request: Please email order@studiomlighint.com with subject line
"Sample Order_ [Project Name] / [Specifier/Designer]"
All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments: