Job Type:







PRODUCT DESCRIPTION

Cylinders of White cased glass are mounted onto a cast aluminum frame of Satin Nickel or Polished Chrome. LED modules evenly illuminate and provide soft yet ample illumination. Multi volt input is standard which allows for installation into commercial applications.

> MEASUREMENTS DIMENSION

BACK PLATE HANGING WEIGHT

LAMPING

INPUT VOLTAGE LUMENS BULB **BULB INCLUDED** DIMMABLE CRI COLOR_TEMP LIGHTING_DIRECTION : 30" W x 4.75" H x 3.5" Ext : 7" W x 4.75" H x 2.25" HCO : 5.03 lb

:120-277V

- : 1,900 Rated (1,550 Del.) 20W LED PCB Integrated , 20W Total
- : (Integrated)
- : Only at 120V with ELV : 90 CRI
- : 3000K
 - : Up/Down

FINISHES OPTION



GLASS White WT

MATERIAL Aluminum, Glass

RATINGS

CETLUS Damp Location ADA



ADDITIONAL

INSTALL UP/DOWN: Any RATED LIFE 50000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



Job Name: Job Type: Quantity: Comments

Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 1.626.956.4209