

# COUNTERMAX MX-LD-D | UNDERCABINET LED DISC

## SM563860


- Surfaced or Recessed installation with 30°swivel
- Available in 3000K Color Temperature, CRI 80+
- Dimmable using standard dimmer
- 35000 rated life hours
- Two 12" wire leads (Black for Anodized Bronze (BRZ) and Brushed Aluminium (AL) finishes, White for White (WT) finish)
- Twist lock connectors
- 24V low voltage lighting system
- Frosted light guard diffuser
- Up to 9 MX-LD-D LED Discs on a single driver

Job Name:	Job Type:
Quantity:	Comments:



### PRODUCT DESCRIPTION

The versatile CounterMax® MX-L-D LED disc features two piece aluminum construction that allows for both surface mounting or recessed installation and are designed for daisy chain installation of up to nine discs on one driver with direct-wire installation. MX-L-D LED discs operate at a fraction of the heat of a halogen or xenon discs and consume less than three watts of electricity. When used in conjunction with the available dimmable driver, MX-L-D LED discs are dimmable using a standard dimmer. This combination of versatility, safety, energy efficiency and dimmability make the MX-L-D LED discs the smart choice for disc lighting.



### MEASUREMENTS

DIMENSIONS : 2.75"D x 0.5"H  
 HANGING WEIGHT : 0.19 lb


### LAMPING

INPUT VOLTAGE : 24V  
 LUMENS : 220 Rated  
 BULB : (1) 2.3W PCB LED (Integrated)  
 DIMMABLE : Triac CL  
 CRI : 80+

*Always consult a qualified electrician before installing any lighting product*

### INCLUDES:

- Two clear mount clips with 3M Tape
- Two mounting screws



Two piece Aluminum Construction for both Surface and Recessed Installation

### OPTIONAL



Extension Cords  
 12" **SM563868 BK, WT**  
 24" **SM563869 BK, WT**



**SM563874**  
 24V 24W Plug-In Driver



**SM563878**  
 CounterMax MX-LD-D 20W CIs II Dim Direct Wire Driver



Extension Cords  
 12" **SM563887 BK, WT**  
 24" **SM563869 BK, WT**

### FINISHES OPTIONS:

- White (WT)
- Anodized Bronze (BRZ)
- Brushed Aluminium (AL)



### MATERIAL:

Aluminum  
 Frosted Acrylic Lens

### RATINGS:

ETL/cETL  
 DRY Location



### ADDITIONAL:

ROTATION : 30° SWIVEL  
 RATED LIFE : 35,000 Hours  
 OPERATING TEMP : -20° C (-4°), 40°C (104°F)  
 PHOTOMETRIC : Report Found Online

# STUDIO•M

For Modifications or Customizations, please email [contract@studiomlighting.com](mailto:contract@studiomlighting.com)

For Sample Request, please email [order@studiomlighting.com](mailto:order@studiomlighting.com) with subject line: "Sample Order\_[Project Name]/[Specifier/Designer]"

All Samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 626.956.4209