Vaportight | SM567535WTDG

PRODUCT DESCRIPTION

The Vapor Tight light fixture is constructed for any environment. With an integrated 4CCT Select switch, toggle between 3000-5000k. Not just CCT Selectable, this model features a wattage selectable switch allowing you to control the brightness of a space and its electrical usage. Ideal for commercial and industrial applications such as garage facilities and stairwells, this product is both vandal proof and constructed for installation in harsher climates.

MEASUREMENTS

DIMENSION	: 48" L x 4" W x 3.5" H
HANGING WEIGHT	: 2.7 lb

LAMPING

INPUT VOLTAGE	: 120-277V
LUMENS	: (6,500 Del.)
BULB	: 30	40	50W LED DC Integrated , 50W Total
BULB INCLUDED	: (Integrated)
DIMMABLE	: Y
CRI	: 90 CRI
COLOR_TEMP	: 30-35-40-50K

FINISHES OPTION

White (WT)

MATERIAL

Steel, Acrylic

RATINGS

cETLus
Damp Location

ADDITIONAL

RATED LIFE 50000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

STUDIO·M

Modifications or Customizations: Please email contract@studiomlighting.com
Sample Request: Please email order@studiomlighint.com with subject line
"Sample Order_ [Project Name] / [Specifier/Designer]"
All samples are subject to Studio M approval and must show proof of project and/or explanation.

StudioMlighting.com - 1.626.956.4209

Job Name:	Job Type:
Quantity:	Comments: