Quantity:





PRODUCT DESCRIPTION

Inconspicuously recessed within its cylindrical house, an extending arm transforms this surface mounted light fixture into an adjustable spotlight. Simply unthread the top half along the seam to extend the frame length and swing the fixture into position. Twist the lens on the face of this fixture to adjust its beam angle spread. Available in Black and White and two apertures that include a mud-in ring for an even cleaner installation.

MEASUREMENTS DIMENSION CANOPY HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP

: 5.25" L x 5.25" W x 4" H : 5.25" W x 0.25" H x 5.25" L : 1.23 lb

: 120-277V : 1,800 Rated (1,790 Del.) : 18W LED DC Integrated , 18W Total : (Integrated) : Triac or ELV at 120V : 90 CRI : 3000K





MATERIAL Aluminum, Glass

RATINGS

cETLus Dry Location CA Title 24



ADDITIONAL

SLOPE: RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighing.com Sample Request: Please email order@studiomlighint.com with subject line "Sample Order_ [Project Name] / [Specifier/Designer]" All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments