





## **PRODUCT DESCRIPTION**

Inconspicuously recessed within its cylindrical house, an extending arm transforms this surface mounted light fixture into an adjustable spotlight. Simply unthread the top half along the seam to extend the frame length and swing the fixture into position. Twist the lens on the face of this fixture to adjust its beam angle spread. Available in Black and White and two apertures that include a mud-in ring for an even cleaner installation.

# **MEASUREMENTS**

DIMENSION : 5.25" L x 5.25" W x 4" H CANOPY : 5.25" W x 0.25" H x 5.25" L

HANGING WEIGHT : 1.23 lb

## LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 1,800 Rated (1,790 Del.)

BULB : 18W LED DC Integrated, 18W Total

**BULB INCLUDED** : (Integrated) DIMMABLE : Triac or ELV at 120V

CRI : 90 CRI COLOR\_TEMP : 3000K

# **FINISHES OPTION**



### MATERIAL

Aluminum, Glass

#### **RATINGS**

cETLus Dry Location CA Title 24







# **ADDITIONAL**

SLOPE:

RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



Job Name	Job Type:
Quantity:	Comments