



PRODUCT DESCRIPTION

Reducing the scale of the classic cylinder sconce is intended for use in applications needed to meet ADA requirements. The sconce profiles extend vertically casting ample light both upwards and downwards. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications.

MEASUREMENTS

DIMENSION : 2.5" W x 7.5" H x 3.25" Ext
BACK PLATE : 4.5" W x 4.5" H x 3.75" HCO
HANGING WEIGHT : 2 lb

LAMPING

INPUT VOLTAGE : 120-277V
LUMENS : 1,400 Rated (1,190 Del.)
BULB : 7W LED DC Integrated , 14W Total
BULB INCLUDED : (Integrated)
DIMMABLE : Triac
CRI : 90 CRI
COLOR_TEMP : 3000K
LIGHTING_DIRECTION : Up & Down

FINISHES OPTION

 Black (BK)

MATERIAL

Aluminum, Glass

RATINGS

cETLus
Wet Location
ADA



ADDITIONAL

INSTALL UP/DOWN: Up
RATED LIFE 25000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

STUDIO•M

Modifications or Customizations: Please email contract@studiomlighting.com
Sample Request: Please email order@studiomlighting.com with subject line
"Sample Order_ [Project Name] / [Specifier/Designer]"
All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments