





PRODUCT DESCRIPTION

This classic cylinder design has been made ultra-thin intending its use in applications requiring ADA compliance. The sconce casts generous lighting both upwards and downwards using dedicated, high-powered LED. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications. Available in Matte Black, Architectural Bronze and White outdoor powder coat finishes. For Dark Sky applications, make use of the optional Dark Sky Cap available.

FINISHES OPTION

-  Architectural Bronze (ABZ)
-  White (WT)

MATERIAL

Aluminum, Glass

RATINGS

cETLus
Wet Location
ADA



ADDITIONAL


INSTALL UP/DOWN: Up
RATED LIFE 25000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)

MEASUREMENTS

DIMENSION : 2.5" W x 19.75" H x 3.25" Ext
BACK PLATE : 4.5" W x 4.5" H x 9.75" HCO
HANGING WEIGHT : 3.3 lb

LAMPING

INPUT VOLTAGE : 120-277V
LUMENS : 1,400 Rated (1,190 Del.)
BULB : 7W LED DC Integrated , 14W Total
BULB INCLUDED : (Integrated)
DIMMABLE : Triac
CRI : 90 CRI
COLOR_TEMP : 3000K
LIGHTING_DIRECTION : Up & Down



*height from center of outlet to the top of the fixture

Always consult a qualified electrician before installing any lighting product.



Modifications or Customizations: Please email contract@studiomlighting.com
Sample Request: Please email order@studiomlight.com with subject line
"Sample Order_ [Project Name] / [Specifier/Designer]"
All samples are subject to Studio M approval and must show proof of project and/or explanation.

Job Name:	Job Type:
Quantity:	Comments: