SM869915

- Suitable for Wet Locations
- 12° +/- .5° Blade Pitch
- Remote Control Option (FCTHAND)
- **ABS Blades**
- Optional Light Kit FKT206 for Damp Locations
- 3 Speeds with Reverse







SN w/Walnut/Pecan

BK w/Walnut/Pecan

UNIVERSAL Wall Remote *Sold Separately Compatible with All Fans (Excl. Fandelights)



FCTHAND








Optional Light Kits

FKT206SN



PRODUCT DESCRIPTION

The Basic-Max ceiling fan features the ability to be installed three different ways: close mount, standard stem, and optional stems up to 72" long.



		LUMENS BLA					BLADE
ITEM#	LAMPING	DIMENSIONS	RATED	DEL	WEIGHT	BLADES	PTICH
SM869915	120V, 4 X 9W LED 3000K	D52" X 18.25"H	2100	1680	14.52 lb	5 x ABS (Included)	12

FKT206BK

Energy Information at High Speeds						
AIRFLOW CFM	AIRFLOW EFFICIENCY	ELECTRICITY USE				
4779 CFM	85 CFM / W	37W				



FINISHES OPTION

BK: Black

OI: Oil Rubbed Bronze

MATERIAL

Steel

RATINGS

CETLUS Damp Location





FAN RODS: (SOLD SEPARATELY)

6" x 3 (Incl.)

12" (FRD18)

18" (FRD24) 24" (FRD30)

36" (FRD36)

48" (FRD48)

60" (FRD60)

72" (FRD72)

ADDITIONAL

OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.

Job Name:



Quantity:	Comments

Job Type: